# A PRO of Industrial Flash Memory Storage www.apro-tw.com



#### Industrial 2.5" form-factor 40/44-pin IDE to CF card adapter

## AD-CF24VIDE0X003R



#### AD-CF24HIDE04003R



#### **Common Specifications:**

-	
> Form-factor	2.5" form-factor with 4 standard 2.5" HDD
	fixed holes
	Vertical type for 40-pin male IDE connector only
	horizontal type for optional 40-pin and/or
	44-pin male IDE connector
Host interface	40-pin (2.45mm pixel) male IDE connector * 1
	44-pin (2.00mm pixel) male IDE connector * 1
⇒ CF Socket	CompactFlash type II socket * 1 each side
▶ Power Connector	40-pin IDE adapter equipped with 4-pin floppy
	power connector
Master/Slave Setup	By jumper
Support Card Types	CompactFlash card type I/II and MicroDrive
Data Transfer Mode	Support PIO mode, DMA mode and up to
	UDMA-4 mode
LED Indicator	Optional for special request
Bootable	Yes
Hot Swappable	No
Operation Voltage	+5V
Supported OS	Compatible with DOS, Windows 3.1/ NT4/
	98SE/ME/ 2000/XP and Linux
Dimension (PCB only)	70.1 mm * 78.1 mm
Weight	55 g / 1.94oz
Warranty	1 year warranty

### **Part Number List**

AD-CF24VIDE0X003R	Host side vertical type 40-pin IDE male connector
	to CF type II socket * 2
AD-CF24HIDE04003R	Host side horizontal type 40-pin IDE male connector+44-pin
	IDE male connector to CF type II socket * 2