

# RM12800

## 1U Mini-ITX Appliance Server Chassis



Rear View



Inside View



Optional  
2 x front 40 mm fans



Flex ATX PSU (180W)



Slim ODD bay or 2.5" HDD  
with SK51102



Optional  
1 x rear 40mm fan



Cable-link riser for  
1 x low profile add-on card

### Features & Benefits

- Support mini-ITX (6.7" x 6.7") M/B
- Support 1 x slim ODD bay and 1 x 3.5" bay
- Optional 3 x 40mm fans for different M/B cooling configurations
- Built-in 180W Flex ATX PSU
- Removable front handle and bracket for non-rackable applications

### Specification

<b>Model Name</b>	• RM12800
<b>M/B Form Factor</b>	• Mini-ITX (6.7" x 6.7")
<b>Dimension (D x W x H)</b>	• 306 x 370 x 43.5 (mm), 12" x 16.9" x 1.7"
<b>Drive Bay</b>	• Exposed: 1 x Slim ODD, 1 x 3.5"
<b>PSU Form Factor</b>	• Flex-ATX, 180W
<b>Indicator</b>	• 1 x Power Status, 1 x HDD Activity, 2 x LAN Activity • 1 x Fan Failure and Overheat
<b>Front Control</b>	• Power On/Off, Alarm Mute, System Reset, 1 x USB 2.0
<b>System Security</b>	• Intrusion Switch
<b>Cooling Fan</b>	• Middle: 2 x 40mm (Option) • Rear: 1 x 40mm (Option)
<b>Slot Opening</b>	• 1 x Low Profile
<b>HDD Backplane</b>	• N/A
<b>Metal Thickness</b>	• 1.2mm
<b>Net Weight</b>	• 2.8kg
<b>Gross Weight</b>	• 4.3kg
<b>Front Bezel</b>	• Option
<b>Cubic Feet</b>	• 1.28
<b>Container Info</b> (Single Packing)	• 20": 790, 40": 1630, 40"H: 1887

### Optional Items

	Order Code	Description
<b>Storage Kits</b>	◆ Note1.	2.5" or 3.5" HDD storage kits
<b>Fan</b>	83H303128-001	40x28mm, PWM,
	83H303127-003	40x28mm, PWM, w/Finger Guard
	◆ Note1. SK41203 / SK51102	

※ PSU ※ M/B Support ※ I/O Gasket ※ Air Duct ※ (Please refer above of information from CHENBRO web)

### Order Information

Order Code	M/B	Backplane	Cooling Fan(mm)	PCI Slot	PSU	Slide Rail
RM12800-180	6.7"x6.7"	N/A	Option	1x LP	180W	N/A