



P630i & P640i

A Complete Security Solution for Tamper-Resistant ID Cards

Adding unique security features to ID cards is easier, faster, and more economical with either the P630i (with single-sided lamination) or the P640i (with dual-sided lamination). This next generation printer delivers missionreliability critical and superior affordability. Protect your ID cards from counterfeiting, alteration or duplication with the P630i or the customizable levels of security. The printer is one of the first manufactured to offer an extended range of security options for all printing components cards, ribbons, laminates and printers. When security counts, count on the P630i or the P640i.

Use the P630i or P640i printer for:

- Agency Licenses
- High Security Access Control ID Cards
- Law Enforcement and Correctional Facility ID Cards
- Airport ID Cards
- Any card application requiring long lasting, secure issuance of tamper-resistant ID's

Many "Best In Class" features:

- Lowest consumables cost per card in the industry
- Highest production output speed with continuous card loading feature
- Superior print quality for optimal colour fidelity and precision details
- Reliable and easy to use

FEATURES

- Full colour dual-sided card printing and single or dual-sided lamination
- Micro card positioning for excellent colour registration and superior print quality
- Numerous security features (convert printing, Secure ID / Key, ID / Log)
- Built-in Ethernet for network capability (optional)





P630i & P640i Technical Details

GENERAL SPECIFICATIONS

- · Dual-sided printing and one-pass waste-free lamination
- 120 cards/hour dual-sided printing and laminating (YMCK ribbon & 1.0mil laminate both sides)
- · Micro-positioning card transport system for enhanced colour photos
- Complete system security features & options for printer, ribbons, laminate, cards, and card issuance process
- · Covert printing capability text approx 17 mil high
- · Automated card cleaning before printing
- · Built-in Ethernet option for networking capability
- Windows® drivers for 2000 and XP with advanced security features (ID/Log & password protection)
- · One year printer warranty
- · One year (unlimited passes) printhead warranty

COLOUR PRINTING

- · Colour dye sublimation and resin K
- · 30 seconds per card (YMCK & dual sided lamination)
- · 300 dpi (11.8 dots/mm) print resolution

BAR CODES

· Bar codes and other symbologies available via Windows driver

FONTS

· True Type or other type fonts via Windows driver

CARD SPECIFICATIONS

- · Types: PVC Composite
- Card width/length: ISO CR-80 ISO 7810 2.12" (54mm) x 3.38" (86mm)
- · HiCo Magnetic Stripe ISO 7811
- · Contact Smart Card ISO 7816 Compliant
- · Card thickness: 27 mil 39 mil
- · Card input hopper capacity: 150 cards

RIBBON SPECIFICATIONS

- YMCK: 600 cards/rollYMCKK: 500 cards/roll
- YMCUvK: 500 cards/roll
 Black: 3000 cards/roll
- Cleaning cartridge: cleans 3,000+ cards

LAMINATE SPECIFICATIONS

- Linerless & wastefree 1.0 mil laminate, 600 cards/roll
- P630i: upper laminate cassette

P640i : two laminate cassettes (upper & lower)

- · Laminates available:
 - clear full size
 - clear for magnetic stripe cards and
 - clear for smart card
- · Custom laminates available upon request:
 - Holographic images
 - Special OVD images
 - UV images

COMMUNICATION INTERFACE

- USB 1.1 (Standard)
- Built-in 10/100 Ethernet (factory installed option)

MECHANICAL

- Width: 27.5" (699mm) not including exit hopper
- Depth: 9.7" (246mm)Height: 11.5" (292mm)
- Weight: 35 lbs (15.9kg)

ELECTRICAL

- 110 240 Volts AC, 50/60 Hz
- · FCC Class A, UL, CUL, & CE approved

ENVIRONMENTAL

- Operating temperature: 50°F to 95°F (10°C to 35°C)
- Operating humidity: 20% to 80% non-condensing
- Storage temperature: -4°F to 158°F (-20°C to 70°C)
- Storage humidity: 5% to 90% non-condensing
- · Ventilation: Free air

OPTIONS

- · ID/Key security printing feature
- · Magnetic Encoder (HiCo only)
- · Smart Card Contact Station
- · Smart Card Contact encoder/reader



Always use TrueColours™ certified media from NBS Technologies





Website: www.nbstech.com
Email: info@nbstech.com

Corporate Headquarters Canada 703 Evans Avenue Toronto, Ontario M9C 5E9 Canada tel: +1 416.621.1911 fax:: +1 416.621.8875

Contact your nearest NBS location for more information on Javelin card printers: United Kingdom For Sales & Technical Support 7 Byfleet Technical Centre Canada Road West Byfleet, Surrey KT14 7/NB United Kingdom tel: +44 (0) 1932.351531 fax: +44 (0) 1932.351382 USA For Sales 70 Eisenhower Drive Paramus, NJ 07652 USA tel: +1 416.840.8620 fax: +1 201.846.6160 USA For Technical Support 10925 Bren Road E Minneapolis, MN 55343 USA tel: +1 952.912.9400 Australia For Sales PO Box 780 Hurstville BC NSW 1481 Australia tel: +61 (2) 9546.6841 fax: +61 (2) 9546.6851